

# BRILLANCEMÈTRE MODÈLE GLOSS60

# ERICHSEN

+33 04 75 60 11 77  
info@erichsen.fr

## DESCRIPTIF TECHNIQUE :

Model: HG60S

Measuring Angle: 60°

Comply with standard ISO 2813, GB/T 9754, ASTM D 523, ASTM D 2457

Measuring Area (mm): 9x15

Measuring Range: 0~200GU

Division Value: 1 GU

Measurement Range: 0-200GU

Repeatability: ±1GU

Reproducibility: ± 1 GU

Measurement Standard: Conform with JJG696 first class glossmeter working requirement

Chromaticity Corresponding: Corresponding with CIE 1931 (2°) under CIE C light source

Errors: ±1.5 , ± 1.5%

Measuring Time: 0.5s

Dimension: L\*W\*H: 160mm\*75mm\*90mm



# BRILLANCEMÈTRE MODÈLE GLOSS60

**ERICHSEN**

+33 04 75 60 11 77  
info@erichsen.fr

Weight: 350g

Language: Chinese/English

Battery: 3200mAh Li-ion Battery, > 10000 times(within 8 hours)

Display: TFT 3.5 inch

Interface: USB/RS-232

Storage: Basic mode: 1000

Operation Temperature: 0~40°C (32~ 104°F)

Storage Temperature: -20~50°C (-4~122°F)

Humidity: <85% relative humidity, no condensation

Standard Accessories: Power Adapter, USB cable, User Manual, Calibration Plate Optional

Accessories: Miniature Printer

Note: The specifications are subject to change without notice

## CONTACT

ERICHSEN

9 Cours Manuel de Falla Z.I. MOZART - 26000 Valence - FRANCE

+33 04 75 60 11 77 - info@erichsen.fr - www.erichsen.fr